

AK912 – Mobile Thermal Printer Bluetooth



Specs	AK912 Description
Print method	Direct thermal line
Printer head	SEIKO(Original)
Resolution	203DPI(384dots/line)
Print speed	40-60mm/s
Character set	ASCII,GB18030(Chinese),BIG5 (support French, English, etc.
Effective printing width	48MM
Print font	12x24, 9x17, Chinese:24x24
Character per line	48-font A / 64-font B
Bar code	1D: UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 - 2D: PDF417,QR CODE, DATA matrix
Graphic	Support bitmap image and logo printing
Memory Printing	YES
Paper End Sensor	YES
Overheating Protection	YES
Interface	RS-232 / USB / Bluetooth
Emulation	ESC/POS; SDK; CPCL
Driver	Windows 7/8/1/XP
Running OS	Windows Mobile, Wince, Android, IOS
Screen	OLCD, Support Chinese and English
Power saving	Auto power saving and 1 second wake up
Detecting	Double black label detect
Battery	1300mAh 7.4v Li-polymer battery
Charging	Re-charger and car-charger(option)
Dimension (LxWxH)	113mm X 84mm(D) X 47mm
Net weight	305G
Gross weight	769G
Paper type	Thermal paper / Thermal label
Paper width	57.5± 0.5mm
Paper roll diameter	MAX 40MM
Roll core inner diameter	13mm(min)
Paper thickness	0.05mm ----0.15mm
Paper loading	Drop in paper loading
Operating Temp/Humidity	-0°C/50°C 10%--80%
Storage Temp/Humidity	-20°C/60°C 10%--90%
Certification	CCC, CE, ROHS
Application	Logistic, warehouses, Convenience Stores, Retails, Supermarkets, etc.